



## BASEBALL FOUL POLE SPECIFICATIONS

### ITEM # - BSFOUL15 - 15' FOUL POLE

The Foul Pole is constructed of two poles; lower section and upper section; along with two 4' sections referred to as wing panels.

#### 1) LOWER POLE -

Constructed of 3.5" outside diameter x .098" wall x 112.0" L galvanized steel tubing.

The pole has a 8.0" swage on the upper end of it to fit with the UPPER POLE. After installation 36.0" of this pole will be below ground level.

#### 2) UPPER POLE -

Constructed of 3.5" outside diameter x .098" wall x 112.0" L galvanized steel tubing.

The pole has a series of 12mm weld nuts for attaching WING PANELS.

#### 3) WING PANELS -

Prefabricated Panels are constructed of

30mm x 30mm x 3mm steel angle iron

40mm x 20mm x 2.5mm diamond mesh flattened expanded metal

#### 4) FINISH -

Powder Coated after fabrication with outdoor Yellow PMS-102C

#### 5) HARDWARE -

Zinc Plated Grade2

#### 6) GROUND SLEEVES (optional) -

Constructed of 4.0" outside diameter x .165" wall x 36.0" L steel tubing. Galvanized after fabrication.

\* FOLLOW SAME CONCRETE DETAIL  
IF OPTIONAL GROUND SLEEVE IS NOT USED.

\* MANUFACTURER RECOMMENDS  
THE FOOTING BE REINFORCED  
WITH 6 PIECES OF 34" REBAR.

<div>TOLERANCE</div> <div>.X = ±.030</div> <div>.XX = ±.010</div> <div>.XXX = ±.005</div> <div>FRACTIONAL = ± 1/32</div> <div>UNLESS OTHERWISE NOTED</div>		<div><div><div><div></div></div><div>BSN SPORTS</div></div><div>1901 Diplomat Drive</div><div>Farmers Branch, Texas 75234</div></div>		
		DRAWN	Z. OSORIO	3/11
		CHECKED		
		APPROVED		
TITLE		BASEBALL FOUL POLE - 15'		
REV A	DATE 1/21			
REF:	SCALE: NTS	NUMBER	BSFOUL15	