






SEATS ARE CONSTRUCTED OF 10" [254 mm] WIDE ANODIZED ALUMINUM. FRAMEWORK IS COMPRISED OF WELDED HEAVY GAUGE STEEL TUBING FOR SUPERIOR SUPPORT AND STRENGTH. END CAPS ARE CONSTRUCTED OF DIE CUT ALUMINUM STRIPS WITH PUNCHED HOLES FOR SCREWS OR RIVETS.



Gared Performance Sports Systems
9200 East 146th Street, Suite A
Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED PERFORMANCE SPORTS SYSTEMS IS STRICTLY PROHIBITED.

7'-6" PORTABLE BENCH W/O BACK

DRAWN CONNERLEY		DATE 8/14/2014	DATE ISSUED 8/14/2014	
APPROVED		DATE		
SIZE A	SCALE	SHT. NO. 1 OF 2	PART NO. BE08PT	REV A

A	JJC	01/23/15
REV	BY	DATE

Bench Specifications: Spectator tm Series

“PT” Portable without Back Model

SECTION 13125

Part 1- General Requirements

- 1.1 Description
 - A. Design and Build of Aluminum and Steel Benches
- 1.2 Quality Assurance
 - A. Manufacturer: Gared Holdings, LLC , 9200 E. 146th St., Noblesville, In 46060
 - B. Qualifications: Manufacturer shall have a minimum of ten years of experience in the design and manufacture of benches
 - C. Welders and Procedures to be AWS certified
- 1.3 Warranty
 - A. Warranty shall include defects in materials and workmanship under normal use and does not apply to work that has been damaged by abuse or natural disaster. Warranty period shall be for a period of 1 Year and begin on date material is received by owner or subcontractors date of completion

Part 2- Products

- 2.1 Design
 - A. Frames: Welded steel tubing spaced at 6’0” (max) intervals
 - B. Seats: (1) nominal 2” x 10” anodized aluminum
- 2.2 Materials and Finishes
 - A. Frames: Heavy Gauge Steel Tubing with hot dipped galvanized finish, ASTM A-123
 - B. Seats: Aluminum alloy 6063-T6 clear anodized 204R1, AA-M10C22A31 , wall thickness of .078
 - C. Hardware: Nuts and bolts to be galvanized
 - D. Accessories: End caps, anodized aluminum 6063-T6 anodized, Mounting clips & splices to be mill aluminum 6061-T6

Part 3- Execution

- 3.1 Installation
 - A. Install product in accordance with manufacturer installation instructions and drawings