



Bench legs shall be constructed of 2" x 2" square aluminum tubing with a 12 ga. wall thickness and polyester powder coated finish. Leg length shall allow 12" bury into a 30" deep concrete footing. All exposed tube ends shall be enclosed by means of molded plastic end caps. Bench shall be 15' in length to accommodate up to 10 players. Seat shall be extruded aluminum with clear anodized finish designed to provide a 10" wide plank with a 1 3/4" overall thickness and have molded end caps. The planks shall have a minimum cross section thickness of .090". Seat and foot planks in excess of 7 1/2' Shall be shipped in 2 or 3 piece sections. Each section shall be connected to the adjoining section at assembly by means of two aluminum extrusion connector tubes, and 8 self drilling, self-threading hex screws. For Powder Coated Aluminum Seat Planks order optional BL15SEAT1-XX for each plank. Choose any combination of colors: Royal, Scarlet, Navy, Forest Green, Black and White. Planks shall be attached to three tubular leg assemblies. All assembly hardware shall be zinc plated. Installation to be completed in accordance to manufacturer's instructions. Do not scale drawings. Bench shall carry a 5-year limited warranty on legs and 2-year limited warranty on aluminum planks and shall weigh 45# BNF1501AA.



PRODUCT SPECIFICATION

BNF1501 15' FIXED PLAYER BENCH

REVISED 11/8/23 L.M.