



System shall consist of a 5" square, 1/8" wall steel support pole, fabricated steel adjustable extension arm, outdoor breakaway goal and 36" x 60" rectangular unbreakable, clear polycarbonate backboard with aluminum frame. Pole shall be shipped in 2 pieces and attached in the middle by means of two 3/8" x 3" x 12" steel bars, and eight 1/2" x 3/4" button head cap screws forming a single, straight, rigid pole. Connecting point shall be covered by pole padding if padding is included in the systems. Rim height shall be indefinitely adjustable from 7 1/2' to official 10' height by means of a hand operated crank located in the front of the pole. The distance from the face of the backboard to the front of the pole shall be 30" when rim is at official 10' height. Support pole shall be installed in a concrete footing at a minimum of 12" diameter and 42" deep. Pole and extension arm shall be powder coated black. Installation shall be completed in accordance with the manufacturer's instructions. Pole and backboard shall carry a 2-year limited warranty. Rim, padding and crank shall carry a 1-year limited warranty. Pole and backboard padding shall be available options. Approximate shipping weight shall be 320#



## PRODUCT SPECIFICATION

PR95UZC ZIPCRANK™ PLAYGROUND ADJUSTABLE SYSTEMS

REVISED 6/4/24 L.M