

VB23 3" Volleyball Floor Socket and Cover Plate Floor sockets shall be extruded aluminum with an interior diameter of 3". Cover plates shall be constructed of machined cast bronze with a hinged lid with a minimum opening of 6". For Hinged Brass Floor Plate order VB23-CV. When assembled for installation, the assembly shall be fixed for a socket depth of 10" from the finished floor to the bottom of the socket. Each assembly shall weigh approximately 8#.

VB26 3-½" Volleyball Floor Socket and Cover Plate Floor sockets shall be extruded aluminum with an interior diameter of 3-½". Cover plates shall be constructed of machined cast bronze with a hinged lid with a minimum opening of 6". For Hinged Brass Floor Plate order VB23-CV. When assembled for installation, the assembly shall be fixed for a socket depth of 10" from the finished floor to the bottom of the socket. Each assembly shall weigh approximately 8#.

VB27 4" Volleyball Floor Socket and Cover Plate Floor sockets shall be extruded aluminum with an interior diameter of 4". Cover plates shall be constructed of machined cast bronze with a hinged lid with a minimum opening of 6". For Hinged Brass Floor Plate order VB23-CV. When assembled for installation, the assembly shall be fixed for a socket depth of 13" from the finished floor to the bottom of the socket. Each assembly shall weigh approximately 8#.